

Tezla LED Fire Rated Downlights

Tezla LED Fire Rated Downlights



Tezla Fire Rated Downlights are designed to the highest standard to maintain the fire rating of your ceiling. These fittings are rated for 30/60/90 minutes with a 30 minute rating on I or Web Joist's. In addition to being fire rated, they are also dimmable and supplied with a CCT switch to change the output colour between 2700, 3000, 4000 and 6000K. This means each fitting can meet 8 possible variations. With an IP rating of IP65 from below, and a 5 year warranty, they are the ideal solution to maintain fire rating on your job.





Tezla LED Fire Rated Downlights

Tezla LED Fire Rated Downlight

CCT-2700/3000/4000/6000

Dimmable

Code	DLFR5
Watt	5W
Lumen Output	535 Lumen

General Information

Mounting Recessed with spring clips

Dimensions84X58mmCut- Out Size65-70mm

Void Requirement 60mm

IP Rating IP65 from Front

30/60/90 Minutes—solid Timber

Fire Rating 30 Minutes—I-Joist

30 Minutes—Web-Joist

Warranty 5 Years

Electrical Information

Voltage 220—240Vac

Driver Output 55mA
Frequency 50/60Hz
Surge Protection 1.5kv

Operating temperature -30 to +50°
Isolation Class II

Connectors Push fit Loop in Loop out

Dimmable Yes—Trailing & Leading Edge

Max pieces per run 10 Pieces

Cable size Suitable for 0.75—2.5mm²























Tezla LED Fire Rated Downlights

TezlaLED Fire Rated Downlight

Performance Data Construction **Energy Rating** Ε Material Aluminium/Iron/Zinc Watt 5 Watt Lens PC **Heat Sink** Extruded Aluminium **Lumen Output** 500 Lumen 100lm/W PC Efficiency (lm/W) **Driver Housing Life Time** 50,000 Hours Bezel **ABS** Warranty 5 Years CRI 80 **Power Factor** 0.85 **Beam Angle** 60° LOR % 90% **CCT Switch** (27003000/4000/6000K) Loop in Loop out Dimmable LED Driver **Push Connector** Fire Rated Seal Spring Clips for Mounting IP65 from Below

