



# Ducting - Rectangular

## 45° Vertical Bend




| Cat. No. | Product Type | External Dimensions |     |     | Resistance (Pa) at flow rate |        |         |        |         |        |        |        |   |
|----------|--------------|---------------------|-----|-----|------------------------------|--------|---------|--------|---------|--------|--------|--------|---|
|          |              | H                   | W   | D   | 8 l/s                        | 13 l/s | 21 l/s  | 29 l/s | 37 l/s  | 45 l/s | 53 l/s | 61 l/s |   |
| 40045    | 110 x 54mm   | -                   | -   | -   | -                            | -      | -       | -      | -       | -      | -      | -      | - |
| 55645    | 204 x 60mm   | -                   | -   | -   | -                            | -      | -       | -      | -       | -      | -      | -      | - |
| Cat. No. | Product Type | H                   | W   | D   | 60 l/s                       |        | 120 l/s |        | 180 l/s |        |        |        |   |
| 60963    | 220 x 90mm   | 110                 | 225 | 115 | 6                            |        | 27      |        | 65      |        |        |        |   |
| 1670     | 225 x 25mm   | -                   | -   | -   | -                            |        | -       |        | -       |        |        |        |   |
| 1690     | 300 x 25mm   | -                   | -   | -   | -                            |        | -       |        | -       |        |        |        |   |

## Horizontal T-Piece - Adaptor to Connect Flat Channel Ducting




| Cat. No. | Product Type | Size       | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |
|----------|--------------|------------|------------------------------|--------|--------|--------|--------|--------|--------|--------|
|          |              |            | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |
| 40080    | 110 x 54mm   | 110 x 54mm | vary on installation         |        |        |        |        |        |        |        |
| 55582    | 204 x 60mm   | 204 x 60mm | vary on installation         |        |        |        |        |        |        |        |

## Cross Over Duct Connector




| Cat. No. | Product Type             | External Dimensions |     |     | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |
|----------|--------------------------|---------------------|-----|-----|------------------------------|--------|--------|--------|--------|--------|--------|--------|
|          |                          | H                   | W   | D   | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |
| 44273    | 30° Drop Down Connection | 120                 | 220 | 210 | 0.2                          | 0.5    | 1.7    | 3.6    | 6.0    | 9.1    | 12.4   | 16.6   |

## Rectangular Wall Plate




| Cat. No. | Product Type | External Dimensions |     |   | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |     |
|----------|--------------|---------------------|-----|---|------------------------------|--------|--------|--------|--------|--------|--------|--------|-----|
|          |              | H                   | W   | D | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |     |
| 41150    | 154 x 154mm  | 154                 | 154 | - | n/a                          | n/a    | n/a    | n/a    | n/a    | n/a    | n/a    | n/a    | n/a |
| 58650    | 172 x 172mm  | 172                 | 172 | - | n/a                          | n/a    | n/a    | n/a    | n/a    | n/a    | n/a    | n/a    | n/a |
| 51150    | 119 x 264mm  | 119                 | 264 | - | n/a                          | n/a    | n/a    | n/a    | n/a    | n/a    | n/a    | n/a    | n/a |

## Flat Channel Connector



| Cat. No. | Product Type | External Dimensions |     |     | Resistance (Pa) at flow rate |        |         |        |         |        |        |        |
|----------|--------------|---------------------|-----|-----|------------------------------|--------|---------|--------|---------|--------|--------|--------|
|          |              | H                   | W   | D   | 8 l/s                        | 13 l/s | 21 l/s  | 29 l/s | 37 l/s  | 45 l/s | 53 l/s | 61 l/s |
| 40200    | 110 x 54mm   | 54                  | 114 | 100 | <1                           | <1     | 1.1     | 1.4    | 2.2     | 3.4    | 4.8    | 6.4    |
| 58200    | 150 x 70mm   | -                   | -   | -   | -                            | -      | -       | -      | -       | -      | -      | -      |
| 55200    | 204 x 60mm   | 64                  | 212 | 100 | <1                           | <1     | <1      | <1     | <1      | <1     | 1.2    | 1.5    |
| 1520     | 225 x 25mm   | -                   | -   | -   | -                            | -      | -       | -      | -       | -      | -      | -      |
| 1530     | 300 x 25mm   | -                   | -   | -   | -                            | -      | -       | -      | -       | -      | -      | -      |
| Cat. No. | Product Type | H                   | W   | D   | 60 l/s                       |        | 120 l/s |        | 180 l/s |        |        |        |
| 60920    | 220 x 90mm   | 95                  | 224 | 52  | <1                           |        | <1      |        | <1      |        |        |        |

## Flat Channel Connector with Internal Damper



| Cat. No. | Product Type             | External Dimensions |     |    | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |
|----------|--------------------------|---------------------|-----|----|------------------------------|--------|--------|--------|--------|--------|--------|--------|
|          |                          | H                   | W   | D  | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |
| 40270    | 110 x 54mm - with Damper | 60                  | 115 | 75 | 16                           | 17.5   | 19.5   | 22     | 25.5   | 30.5   | 36     | 42     |

## Rigid Duct Attenuator



| Cat. No. | Product Type | Size       | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |   |      |
|----------|--------------|------------|------------------------------|--------|--------|--------|--------|--------|--------|--------|---|------|
|          |              |            | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |   |      |
| SL55105  | 0.6m Length  | 204 x 60mm | <1                           | <1     | 2.3    | 4.2    | -      | -      | -      | -      | - | 12.2 |
| SL55100  | 1.0m Length  | 204 x 60mm | <1                           | <1     | 2.2    | 4.1    | -      | -      | -      | -      | - | 15   |

## Insulated Rectangular Duct



| Cat. No.  | Product Type | Size       | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |   |   |
|-----------|--------------|------------|------------------------------|--------|--------|--------|--------|--------|--------|--------|---|---|
|           |              |            | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |   |   |
| IJRP55150 | 1.5m Length  | 204 x 60mm | <1                           | <1     | 1.3    | 2.2    | 3.3    | 4.5    | 5.9    | 7.8    | - | - |
| IJRP55020 | 2.0m Length  | 204 x 60mm | -                            | -      | -      | -      | -      | -      | -      | -      | - | - |
| IJRP60915 | 1.5m Length  | 220 x 90mm | -                            | -      | -      | -      | -      | -      | -      | -      | - | - |

## Insulated Vertical Bend

| Cat. No.  | Product Type      | Size       | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |   |   |
|-----------|-------------------|------------|------------------------------|--------|--------|--------|--------|--------|--------|--------|---|---|
|           |                   |            | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |   |   |
| IJBV55645 | Vertical 45° Bend | 204 x 60mm | 0.1                          | 0.5    | 1.3    | 2.5    | 4.4    | 6.9    | 10     | 13.3   | - | - |
| IJBV55600 | Vertical 90° Bend | 204 x 60mm | 1.1                          | 2.5    | 5.2    | 9.8    | 16.1   | 24     | 33.6   | 45     | - | - |

## Insulated Horizontal Bend



| Cat. No.  | Product Type        | Size       | Resistance (Pa) at flow rate |        |         |        |         |        |        |        |   |   |
|-----------|---------------------|------------|------------------------------|--------|---------|--------|---------|--------|--------|--------|---|---|
|           |                     |            | 8 l/s                        | 13 l/s | 21 l/s  | 29 l/s | 37 l/s  | 45 l/s | 53 l/s | 61 l/s |   |   |
| IJBH55810 | Horizontal 45° Bend | 204 x 60mm | 0.2                          | 0.7    | 1.2     | 2.1    | 3.8     | 6.1    | 9.2    | 13     | - | - |
| IJBH55500 | Horizontal 90° Bend | 204 x 60mm | 0.7                          | 1.7    | 4.1     | 8.4    | 13      | 18     | 25     | 34     | - | - |
| Cat. No.  | Product Type        | Size       | 60 l/s                       |        | 120 l/s |        | 180 l/s |        |        |        |   |   |
| IJBH60950 | Horizontal 90° Bend | 220 x 90mm | 9                            |        | 36      |        | 80      |        |        |        |   |   |

## Insulated T-Piece Bend




| Cat. No.  | Product Type | Size       | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |
|-----------|--------------|------------|------------------------------|--------|--------|--------|--------|--------|--------|--------|
|           |              |            | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |
| IJTH55582 | T-Piece      | 204 x 60mm | vary on installation         |        |        |        |        |        |        |        |

# Ducting - Adaptors

## Elbow 90° Bend M to F


Connector for joining Round Pipe, Flexi Hose & Flat Channel Ducting



| Cat. No. | Product Type         | External Dimensions |     |     | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|----------|----------------------|---------------------|-----|-----|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|          |                      | H                   | W   | D   | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 40300    | 100mmØ to 110 x 54mm | 90                  | 115 | 140 | 3                            | 8      | 17.7   | 33     | 49.9   | 74.5   | 101    | 137    |  |
| 58400    | 125mmØ to 150 x 70mm | -                   | -   | -   | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 54400    | 100mmØ to 204 x 60mm | 80                  | 215 | 195 | 2.9                          | 7.1    | 15.1   | 28     | 45.1   | 68.1   | 92.2   | 118    |  |
| 55400    | 125mmØ to 204 x 60mm | 80                  | 215 | 195 | 3.1                          | 5.9    | 12.2   | 25     | 43.6   | 62.2   | 86     | 111    |  |
| 56400    | 150mmØ to 204 x 60mm | 80                  | 215 | 195 | 2.8                          | 4.9    | 11.6   | 21     | 31     | 41     | 53     | 67     |  |
| 60941    | 100mmØ to 220 x 90mm | 118                 | 226 | 240 | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 60951    | 125mmØ to 220 x 90mm | 118                 | 226 | 240 | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 60961    | 150mmØ to 220 x 90mm | 11                  | 226 | 240 | -                            | -      | -      | -      | -      | -      | -      | -      |  |

## Short to Round Rectangular Adaptor

with male/female adaptors for Connecting Flat Channel Ducting to Round Hose



| Cat. No. | Product Type            | External Dimensions |     |     | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|----------|-------------------------|---------------------|-----|-----|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|          |                         | H                   | W   | D   | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 40700    | 100mm to 110 x 54mm (F) | 60                  | 110 | 105 | 1.2                          | 4.3    | 8.4    | 20     | 30.2   | 43     | 62     | 88     |  |
| 40710    | 100mm to 110 x 54mm (M) | 60                  | 110 | 105 | 1.2                          | 4.3    | 8.4    | 20     | 30.2   | 43     | 62     | 88     |  |

## Round to Rectangular Adaptor - Adaptor to Connect Flat Channel Ducting



| Cat. No. | Product Type         | External Dimensions |     |     | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|----------|----------------------|---------------------|-----|-----|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|          |                      | H                   | W   | D   | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 40701    | 100mmØ to 110 x 54mm | 100                 | 115 | 180 | 1.2                          | 4.2    | 8.3    | 19.8   | 29.9   | 42     | 60     | 86     |  |
| 58701    | 125mmØ to 150 x 70mm | -                   | -   | -   | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 55710    | 125mmØ to 204 x 60mm | 140                 | 210 | 215 | 1.0                          | 1.96   | 3.2    | 4.9    | 6.7    | 8.7    | 11.2   | 14.5   |  |
| 55700    | 150mmØ to 204 x 60mm | 140                 | 210 | 213 | <1                           | <1     | 1.5    | 2.8    | 4.5    | 6.7    | 9      | 11.5   |  |
| 60970    | 150mmØ to 220 x 90mm | 160                 | 225 | 203 | -                            | -      | -      | -      | -      | -      | -      | -      |  |


## Adaptor - Adaptor to Connect Round Pipe Ducting



| Cat. No. | Product Type   | External Dimensions |   |   | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|----------|----------------|---------------------|---|---|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|          |                | H                   | W | D | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 54544    | 125mm to 100mm | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |

## Offset Reducer

Adaptor to Connect Round Pipe Ducting



| Cat. No. | Product Type            | External Dimensions |   |   | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|----------|-------------------------|---------------------|---|---|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|          |                         | H                   | W | D | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 45644    | 150mm to 125mm or 100mm | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |

## Circular Reducer

Adaptor to Connect Round Pipe Ducting, Flexi Hose & Fan Spigots




| Cat. No. | Product Type   | External Dimensions |   |   | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|----------|----------------|---------------------|---|---|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|          |                | H                   | W | D | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 54119    | 125mm to 100mm | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 65118    | 150mm to 125mm | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 86117    | 200mm to 150mm | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 98116    | 250mm to 200mm | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 12800    | 300mm to 200mm | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 40419    | 110mm to 100mm | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |

## Rubber Spigot Adaptor - Adaptor to Connect Cookerhood Spigots




| Cat. No. | Product Type   | External Dimensions |   |   | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|----------|----------------|---------------------|---|---|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|          |                | H                   | W | D | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 50519    | 120mm to 125mm | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |

## Plenum Cooker Hood/Fan - with Connector



| Cat. No. | Product Type | External Dimensions |   |   | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|----------|--------------|---------------------|---|---|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|          |              | H                   | W | D | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 1640     | 100mm        | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 1650     | 100mm        | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 1645     | 120mm        | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 1655     | 120mm        | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |


## Round to Rectangular Adaptor - Requires 414C Connector



| Cat. No. | Product Type        | External Dimensions |   |   | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|----------|---------------------|---------------------|---|---|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|          |                     | H                   | W | D | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 40725    | 100mm to 225 x 25mm | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 40730    | 105mm to 300 x 25mm | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |

# Ducting - Adaptors


## Double Airbrick



| Cat No. | Product Type            | External Dimensions |     |    | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|---------|-------------------------|---------------------|-----|----|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|         |                         | H                   | W   | D  | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 60905W  | 220 x 90mm White        | 145                 | 245 | 80 | 0.2                          | 1.6    | 4.3    | 8.7    | 13.9   | 21.1   | 27.5   | 37.4   |  |
| 60905B  | 220 x 90mm Brown        | 145                 | 245 | 80 | 0.2                          | 1.6    | 4.3    | 8.7    | 13.9   | 21.1   | 27.5   | 37.4   |  |
| 60905CS | 220 x 90mm Cotswold St. | 145                 | 245 | 80 | 0.2                          | 1.6    | 4.3    | 8.7    | 13.9   | 21.1   | 27.5   | 37.4   |  |
| 60905T  | 220 x 90mm Terracotta   | 145                 | 245 | 80 | 0.2                          | 1.6    | 4.3    | 8.7    | 13.9   | 21.1   | 27.5   | 37.4   |  |

## Double Airbrick Adaptor to Rectangular Duct


Fits High Performance Ducting 220 x 90mm to double Airbrick 60905



| Cat No. | Product Type            | External Dimensions |   |   | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|---------|-------------------------|---------------------|---|---|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|         |                         | H                   | W | D | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 60977   | Double Airbrick Adaptor | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |

## Double Airbrick Adaptor to Round Duct


Fits 100/125/150mm Round Pipe



| Cat No. | Product Type            | External Dimensions |   |   | Resistance (Pa) at flow rate |   |   |         |   |   |         |   |  |
|---------|-------------------------|---------------------|---|---|------------------------------|---|---|---------|---|---|---------|---|--|
|         |                         | H                   | W | D | 60 l/s                       |   |   | 120 l/s |   |   | 180 l/s |   |  |
| 60954   | Double Airbrick Adaptor | -                   | - | - | -                            | - | - | -       | - | - | -       | - |  |

## High Performance Ducting Adaptor


Fits 125 Channel Ducting 220x90mm to High Performance Ducting



| Cat No. | Product Type | External Dimensions |   |   | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|---------|--------------|---------------------|---|---|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|         |              | H                   | W | D | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 60957   | Adaptor      | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |


## Airbrick Adaptor

To connect Flat Channel Ducting and Airbrick Ventilators




| Cat No. | Product Type | External Dimensions |   |   | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|---------|--------------|---------------------|---|---|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|         |              | H                   | W | D | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 1580    | Adaptor      | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 1590    | Adaptor      | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |

## Extended Horizontal Airbrick - For 225mm to 300mm System



| Cat No. | Product Type                | External Dimensions |   |   | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|---------|-----------------------------|---------------------|---|---|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|         |                             | H                   | W | D | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 1572    | Fits Direct to Flat Channel | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 1573    | Fits Direct to Flat Channel | -                   | - | - | -                            | -      | -      | -      | -      | -      | -      | -      |  |

## Slimline Airbrick




| Cat. No. | Product Type      | Size     | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|----------|-------------------|----------|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|          |                   |          | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 45010*   | Horizontal Louvre | 110x54mm | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 45011    | Vertical Louvre   | 110x54mm | -                            | -      | -      | -      | -      | -      | -      | -      |  |

\* Fits into airbrick adaptor - 40770

## Slimline Airbrick

Wall Outlet



| Cat. No. | Product Type            | Size     | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|----------|-------------------------|----------|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|          |                         |          | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 55010    | Horizontal Louvre       | 204x60mm | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 55011    | Vertical Louvre         | 204x60mm | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 55012    | Low resistance airbrick | 204x60mm | -                            | -      | -      | -      | -      | -      | -      | -      |  |

## Slimline Airbrick with Internal Damper



| Cat. No. | Product Type      | Size     | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|----------|-------------------|----------|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|          |                   |          | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 58501    | Horizontal Louvre | 150x70mm | -                            | -      | -      | -      | -      | -      | -      | -      |  |
| 55501    | Horizontal Louvre | 204x60mm | -                            | -      | -      | -      | -      | -      | -      | -      |  |

## Airbrick Adaptor

For use with Flat Channel Ducting and Slimline Air Bricks



| Cat. No. | Product Type     | Size     | Resistance (Pa) at flow rate |        |        |        |        |        |        |        |  |
|----------|------------------|----------|------------------------------|--------|--------|--------|--------|--------|--------|--------|--|
|          |                  |          | 8 l/s                        | 13 l/s | 21 l/s | 29 l/s | 37 l/s | 45 l/s | 53 l/s | 61 l/s |  |
| 40770    | Airbrick Adaptor | 110x54mm | -                            | -      | -      | -      | -      | -      | -      | -      |  |

\* Fits airbrick 45010